



CENTRAL VACUUM CLEANING SYSTEMS A SIMPLE BUT EFFECTIVE CONCEPT FOR SEAFARING AND FOR A CLEAN ENVIRONMENT.

The air quality inside these types of structures has to be handled appropriately in order to prevent bacteria, mold, viruses and disease-causing agents to reproduce.

During the process of planning the correct amount of attention is paid to the permanent systems of daily cleaning. Our systems cannot only be used for cleaning but also to power the air exchange system which could otherwise be clogged by the recycled air.

REMOVES DUST
COMPLETELY

RETRACTABLE
HOSE SYSTEM



Evo550



Matrix





EVO 550

Simultaneous operators	1
Max. tubing lenght	100 mt
Max. no. of inlet valves	10 - 15
Motor power	1,5 KW
Surface up to	350 m ²
Voltage requirement	230 V
EC safety degree	IP40
Suction power max.	302 mBar
Airflow max.	199 m ³ /h
Airwatts at ø32 mm	W658
Filter surface	8.000 cm ²
Dust receptacle capacity	20 lt.
Dimensions	ø32 x 90 cm
Sound level	60 dB
Net weight	16 kg



MATRIX

Simultaneous operators	1
Max. tubing lenght	30 mt
Max. no. of inlet valves	3 - 4
Motor power	1,5 KW
Surface up to	130 m ²
Voltage requirement	230 V
EC safety degree	IP55
Suction power max.	260 mBar
Airflow max.	220 m ³ /h
Airwatts at ø32 mm	W421
Filter surface	3.350 cm ²
Dust receptacle capacity	11 lt.
Dimensions	23x39x50 cm
Sound level	59 dB
Net weight	7,5 kg